



## Point by Maharam

### **Abrasion**

App. 35.000 rubs acc. to the Martindale method,  
EN ISO 12947

### **Pilling**

Note 3, EN ISO 12945

### **Lightfastness**

Note 5-7, ISO 105-B02

### **Flame resistance**

EN 1021-1/2

BS 5852 part 1 ignition source 0

US Cal. Tech. Bull. 117

NFPA 260

Crib 5 when flameprotected

No use of brominated flameretardants

### **Quality benefits**

Good abrasion

Good lightfastness

Flame retardant

### **Environmental benefits**

No use of AZO dyes, which may split off  
carcinogenic acrylamines

No use of dyes containing heavy metals/  
complies with ETAD norm

We adhere to the limits set by the Danish Environmental  
Protection Agency's 'List of Undesirable Substances'

Complies with REACH regulation

### **Reduced Emissions**

Greenguard and Greenguard Gold certified

[www.greenguard.org](http://www.greenguard.org)

For further information

[www.kvadrat.dk](http://www.kvadrat.dk)

### **Point by Maharam**

Design: Paul Smith

Type: Upholstery

Composition: 97% viscose (rayon), 3% nylon

Yarn type: Spun

Binding: Jacquard

Width: 135 cm

Weight: Approximately 840 g/lin.m

Repeat: 29-79 cm depending on colourway

Cleaning: Vacuum and dry clean

Stain removal: See special guide