



## Frost

### Lightfastness

Note 5-7, ISO 105-B02

### Flame resistance

EN 13 773 class 1  
BS 5867 part 2 type B  
DIN 4102 B1  
SN 198 898 5.2  
NF D 92 507 M1  
UNI 9177 classe 1  
NFPA 701  
AS/NZS 1530.3  
IMO A.471 (XII)

No use of brominated flameretardants

### Quality benefits

Good lightfastness

Permanent flame retardant

Washable

### Environmental benefits

No use of AZO dyes, which may split off carcinogenic acrylamines

No use of dyes containing heavy metals/complies with ETAD norm

No content of formaldehyde

We adhere to the limits set by the the Danish Environmental Protection Agency's 'List of undesirable substances'

Complies with REACH regulation

For further information

[www.kvadrat.dk](http://www.kvadrat.dk)

### Frost

Design: Alfredo Häberli

Type: Curtain, panel curtain

Composition: 50% polyester FR, 50% polyester

Yarn type: Filament

Binding: Plain

Width: App. 300 cm


Weight: App. 150 g/lin.m

Cleaning: Washable at max. 60°C. Drip drying

Ironing will be necessary

Shrinkage: App. 1% when washed at 60°C

Stain removal: See special guide



 10 year warranty