

Received: 03/03/2008 Completed: 03/04/2008 Letter: II rb P.O.#: Test Report #: 2-72297-1-

Client's Identification: Herringbone Stripe

Tested For: **Kara D'Angelo** Key Test: NFPA 260 Cover Fabric (BLDG) 105  
 Maharam  
 251 Park Avenue South Tel: 1-(212)-614-2977 Ext:  
 New York, NY 10010 Fax: 1-(212)-982-9221

PC: 4H /jd

TEST PERFORMED: NFPA 260 Standard Methods of Tests and Classification System for Cigarette Ignition Resistance of Components of Upholstered Furniture; Cover Fabric Test

RESULTS:	TEST		RETEST (If Required)		
	Specimen #	Ignition (yes/no/SE)	Char Length On Vertical Panel (mm)	Ignition (yes/no/SE)	Char Length On Vertical Panel (mm)
	1	SE	10	SE	12
	2	NO	12		
	3	SE	10	SE	10

ABBREVIATION WHICH MAY BE USED:

SE: Indicates that the cigarette self extinguished prior to burning its entire length. When this occurs, a "retest" of that specimen is performed.

REMARKS: None.

CLASSIFICATION SYSTEM:

Class I - For each specimen: No obvious ignition; maximum char length 45 mm (1.75"). (Indicates propensity to resist cigarette ignition in conjunction with standard foam filling material.)

Class II - For any specimen: Obvious ignition; or char length exceeding 45 mm (1.75"). (Indicates inability to resist cigarette ignition in conjunction with standard foam filling material.)

CONCLUSION: Based on the above Results and Classification System, the item tested is assigned a:

Class I rating;  Class II rating



Received:03/03/2008	Completed:03/04/2008	Letter: II	rb	P.O.#:	Test Report #:	2-72297-1-
---------------------	----------------------	------------	----	--------	----------------	------------

Client's Identification	Herringbone Stripe
-------------------------	--------------------

Tested For: <b>Kara D'Angelo</b> Maharam 251 Park Avenue South New York, NY 10010	Key Test: NFPA 260 Cover Fabric (BLDG) 105  Tel: 1-(212)-614-2977 Fax: 1-(212)-982-9221
--	--

CODE INFORMATION: In accordance with --

- (1) The 2006 Edition of the NFPA Life Safety Code 101 paragraph 10.3.2.1(1);
- (2) The 2006 Edition of the International Fire Code, paragraph 805.1.1.1, 805.2.1.1 and 805.3.1.1

Upholstered furniture components shall be Class I when tested in accordance with NFPA 260, when used in:

- Detention or correctional occupancy
- Health care occupancy
- Residential board & care occupancy

In certain situations an exception is made if the rooms or areas are sprinklered.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by NFPA 260.

*Heather E. Robertson*

AUTHORIZED SIGNATURE  
THE GOVMARK ORGANIZATION, INC. /jb

**MS. HEATHER ROBERTSON**

(Page 2 of 2)