



Hint

Design: Giulio Ridolfo

Type: Screen and wallcovering
Composition: 100% polyester FR
Yarn type: Filament
Binding: Plain
Width: Approximately 67 inches (170 cm)
Weight: Approximately 500 g/lin.m
Repeat: None

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week.
Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary.

More info: Maintenance instruction – please see website,
kvadrat.dk/care-and-maintenance



10 year
warranty



Hint

Pilling

Note 4-5, EN ISO 12945

Seam slippage

Warp: 2.0 mm Weft: 2.0 mm

Lightfastness

Note 5-6 ISO 105-B02

Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 4-5 ISO 105-X12

Absorption

0.55/Class D (flat), 0.85/Class B (waved) EN ISO 354

Airflow

613 Pa s/m EN 29053

Flame resistance

AS/NZS 3837 class 1

ASTM E84 Class A

EN 13501 B, s1, d0

JIS L 1091 A-1D

Quality benefits

Very good lightfastness
Permanent flame retardant
Acoustic performance

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions
Complies with REACH regulation
Environmental Product Declaration (EPD)
Health Product Declaration (HPD)

Reduced emissions

Greenguard and Greenguard Gold certified
greenguard.org

Warranty

10 years. See terms and conditions on kvadrat.dk

For further information
kvadrat.dk