



Diorama

Lightfastness

Note 5-7 ISO 105-B02

Absorption

0.50/Class C (flat), 0.70/Class C (waved) EN ISO 354

Airflow

388 Pa s/m EN 29053

Flame resistance

BS 5867 part 2 type B

DIN 4102 B1

EN 13 773 class 1

EN 13501 B-s1, d0

IMO FTP Code 2010:Part 7

NF D 92 507 M1

SN 198 898 5.2

UNI 9177 classe 1

Quality benefits

Very good lightfastness

Permanent flame retardant

Washable

Acoustic performance

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

No content of formaldehyde

No use of halogen based flame retardants (incl. brominated and chlorinated)

Not bleached

Complies with REACH

Reduced emissions

Greenguard and Greenguard Gold certified

www.greenguard.org

For further information

kvadrat.dk

Diorama

Design: Margrethe Odgaard

Type: Curtain

Composition: 100% Trevira CS

Yarn type: Staple

Binding: Satin

Width: App. 320 cm

Weight: App. 740 g/lin.m

Repeat: 0 cm V, app. 162.5 cm H

Horizontal block stripes and vertical pinstripes when confectioned floor-to-ceiling

Cleaning: Washing at max. 60°C. Drip drying.

Shrinkage app. 1% when washed at 60°C.

Ironing might be necessary

More info: Maintenance instruction—please see website

Colour difference may occur



10 year warranty 