



# Maple

## Abrasion

Approximately 30.000 Martindale rubs, EN ISO 12947

## Pilling

Note 4-5, EN ISO 12945

## Lightfastness

Note 5-7, ISO 105-B02

## Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 4-5 ISO 105-X12

## Flame resistance

EN 1021-1/2

BS 5852 part 1

IMO FTP Code 2010 Part 8

## Maple

Design: Åsa Pärson

Type: Upholstery, low traffic contract and soft seating

Composition: 81% viscose, 15% linen, 4% polyester,  
non-woven polyester backing

Yarn type: Spun yarns

Binding: Plain

Width: App. 140 cm (App. 55 inches)

Weight: App. 850 g/lin.m

Repeat: None



 **10 year**  
warranty

## Quality benefits

Good abrasion

Good lightfastness

Flame retardant

## Environmental benefits

Sustainable fibres

No use of AZO dyes, which may split off  
carcinogenic acryl amines

No use of dyes containing heavy metals/  
complies with ETAD norm

Complies with REACH

## Reduced emission

Greenguard and Greenguard Gold certified

[www.greenguard.org](http://www.greenguard.org)

## Cleaning and maintenance

Maple is constructed from chenille yarns, which create a subtle three-dimensional expression on the textile's surface. As a result, shading and pressure marks will occur during usage and cleaning. These are typical properties of chenille textiles.

We recommend to vacuum the textile frequently by using the upholstery brush or, alternatively, brushing the textile with a soft brush.

Darker spots from water spills or as a result of stain removal can occur. In addition, pressure marks can occur during usage.

Spots and pressure marks can be removed by brushing the textile with a soft brush in moist condition and in direction of the pile. Moisten the textile by placing a damp cloth on the whole surface or spraying it with distilled water. Let the textile dry completely before usage.

For further information  
[kvadrat.dk](http://kvadrat.dk)