



### Relay by Maharam

Design: Maharam Design Studio

Type: Upholstery

Composition: 100% polyester

Yarn type: -

Binding: Plain

Width: Approximately 54 inches (137 cm)

Weight: Approximately 1200 g/lin.m

Repeat: App. 1 cm V, 3 cm H

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week.  
Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary.

More info: Maintenance instruction – please see website, [kvadrat.dk/care-and-maintenance](http://kvadrat.dk/care-and-maintenance)



## Relay by Maharam

### Abrasion

Approx. 30.000 Martindale rubs, EN ISO 12947

Approx. 100.000 double rubs, Wyzenbeek method

### Pilling

Note 4, EN ISO 12945

### Lightfastness

Note 4-7 ISO 105-B02

### Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 4-5 ISO 105-X12

### Flame resistance

BS 5852 Part 1 with treatment \*

EN 1021-1

EN 1021-1/2 with treatment \*

US Cal. Bull. 117-2013

*\* To pass this test flame retardant treatment is necessary.  
We are looking into more environmental friendly alternatives  
but for now the external finisher may use a treatment  
containing halogen based flame retardants*

### Quality benefits

Very good abrasion

Good lightfastness

### Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye  
and heavy metal restrictions

Complies with REACH regulation

### Reduced emissions

Greenguard and Greenguard Gold certified  
[greenguard.org](http://greenguard.org)

### Warranty

3 years. See terms and conditions on [maharam.com](http://maharam.com)

For further information  
[kvadrat.dk](http://kvadrat.dk)